

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



HR1 - ONE WIRE MEDIUM PRESSURE HOSE

Exceeds the requirements of SAE 100R1AT; EN 853 1SN					ONE WIRE BRAID REINFORCEMENT			
NITRILE INNER TUBE					POLYCHLOROPRENE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR1-03	3/16"	0.47	11.9	3,630	14,520	3.5	0.12	B2
HR1-04	1/4"	0.53	13.6	3,270	13,080	4.0	0.15	B2
HR1-05	5/16"	0.60	15.1	3,120	12,480	4.5	0.17	B2
HR1-06	3/8"	0.69	17.5	2,615	10,460	5.0	0.22	B2
HR1-08	1/2"	0.81	20.7	2,320	9,280	7.0	0.28	B2
HR1-10	5/8"	0.94	23.8	1,890	7,560	8.0	0.33	B2
HR1-12	3/4"	1.10	27.8	1,530	6,120	9.5	0.41	B2
HR1-16	1"	1.41	35.8	1,280	5,120	12.0	0.62	B2
HR1-20	1-1/4"	1.70	43.1	920	3,680	16.5	0.84	S4/SG
HR1-24	1-1/2"	1.98	50.3	730	2,920	20.0	1.05	S4/SG
HR1-32	2"	2.51	63.8	580	2,320	25.0	1.48	S4/SG



HR2 - MEDIUM PRESSURE TWO WIRE HOSE

Exceed the requirements of SAE 100R2AT; EN 853 2SN					TWO WIRE BRAID RIENFORCEMENT			
NITRILE INNER TUBE					POLYCHLOROPRENE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR2-03	3/16"	0.48	12.3	6,000	24,000	3.5	0.20	B2
HR2-04	1/4"	0.59	15.1	5,800	23,200	4.0	0.24	B2
HR2-06	3/8"	0.75	19.1	4,800	19,200	5.0	0.34	B2
HR2-08	1/2"	0.88	22.2	4,000	16,000	7.0	0.43	B2
HR2-10	5/8"	1.00	25.4	330	14,520	8.0	0.50	B2
HR2-12	3/4"	1.16	29.4	3,120	12,480	9.5	0.61	B2
HR2-16	1"	1.50	38.1	2,400	9,600	12.0	0.88	B2
HR2-20	1-1/4"	1.86	47.2	1,820	7,280	16.5	1.53	S4/SG
HR2-24	1-1/2"	2.11	54.1	1,310	5,240	20.0	1.64	S4/SG
HR2-32	2"	2.62	66.7	1,160	4,640	25.0	2.03	S4/SG

HOSE

HOSE

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



HR16 - HIGH PRESSURE COMPACT TWO WIRE HOSE								
Exceeds the requirements of SAE 100R16; EN 857 2SC					TWO WIRE BRAID REINFORCEMENT			
NITRILE INNER TUBE					POLYCHLOROPRENE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR16-04	1/4"	0.54	13.7	5,800	23,200	2.0	0.18	B2
HR16-05	5/16"	0.63	16.0	5,075	20,300	2.2	0.25	B2
HR16-06	3/8"	0.70	17.7	5,000	20,000	2.5	0.27	B2
HR16-08	1/2"	0.81	20.6	5,000	20,000	3.5	0.36	B2
HR16-10	5/8"	0.95	24.2	4,000	16,000	4.0	0.41	B2
HR16-12	3/4"	1.10	28.0	3,500	14,000	5.0	0.55	B2
HR16-16	1"	1.40	35.5	2,700	10,800	6.0	0.83	B2
HR16-20	1-1/4"	1.74	44.3	1,813	7,252	8.3	1.12	S4/SG



HXR16SC - EXTENDED LIFE HIGH PRESSURE COMPACT TWO WIRE HOSE								
Exceeds the requirements of SAE 100R16; EN 857 2SC				TWO WIRE BRAID REINFORCEMENT				
NITRILE INNER TUBE				EXTRA ABRASION RESISTANT SYNTHETIC RUBBER				
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HXR16SC-04	1/4"	0.54	13.7	5,800	23,200	2.0	0.18	B2
HXR16SC-06	3/8"	0.70	17.7	5,000	20,000	2.5	0.27	B2
HXR16SC-08	1/2"	0.81	20.6	5,000	20,000	3.5	0.36	B2
HXR16SC-10	5/8"	0.95	24.2	4,000	16,000	4.0	0.41	B2
HXR16SC-12	3/4"	1.10	28.0	3,500	14,000	5.0	0.55	B2
HXR16SC-16	1"	1.40	35.50	2,700	10,800	6.0	0.83	B2

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB

HOSE

HOSE



HR17 - CONSTANT PRESSURE TWO WIRE HOSE								
Exceeds the requirements of SAE 100R17				ONE/TWO WIRE BRAID REINFORCEMENT				
NITRILE INNER TUBE				SYNTHETIC RUBBER OUTER COVER				
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR17-04	1/4"	0.50	12.7	3,045	12,180	2.0	0.11	B2
HR17-06	3/8"	0.65	16.5	3,045	12,180	2.5	0.17	B2
HR17-08	1/2"	0.70	19.8	3,045	12,180	3.5	0.28	B2
HR17-10	5/8"	0.95	24.1	3,045	12,180	4.0	0.41	B2
HR17-12	3/4"	1.13	28.7	3,045	12,180	5.0	0.55	B2
HR17-16	1"	1.44	36.6	3,045	12,180	6.0	0.82	B2



HDR1SN - HIGH TEMP ONE WIRE MEDIUM PRESSURE HOSE								
Exceeds the requirements of SAE 100R1AT; EN 853 1SN				ONE WIRE BRAID REINFORCEMENT				
CHLORINATED POLYETHYLENE INNER TUBE				CHLORINATED POLYETHYLENE OUTER COVER				
-40°F to 302°F (-40°C to 150°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HDR1SN-04	1/4"	0.52	13.1	3,270	13,080	4.0	0.15	B2
HDR1SN-06	3/8"	0.67	17.1	2,615	10,460	5.0	0.22	B2
HDR1SN-08	1/2"	0.80	20.3	2,320	9,280	7.0	0.28	B2
HDR1SN-10	5/8"	0.92	23.4	1,890	7,560	8.0	0.33	B2
HDR1SN-12	3/4"	1.08	27.4	1,530	6,120	9.5	0.41	B2
HDR1SN-16	1"	1.39	35.3	1,280	5,120	12.0	0.62	B2
HDR1SN-20	1-1/4"	1.70	43.1	920	3,680	16.5	0.84	S4/SG
HDR1SN-24	1-1/2"	1.97	50.1	730	2,920	20.0	1.09	S4/SG
HDR1SN-32	2"	2.50	63.6	580	2,320	25.0	1.34	S4/SG

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



HDR2SN - HIGH TEMP MEDIUM PRESSURE TWO WIRE HOSE								
Exceed the requirements of SAE 100R2AT; EN 853 2SN					TWO WIRE BRAID RIENFORCEMENT			
CHLORINATED POLYETHYLYNE INNER TUBE					CHLORINATED POLYETHYLYNE OUTER COVER			
-40°F to 302°F (-40°C to 150°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HDR2SN-04	1/4"	0.59	15.1	5,800	23,200	4.0	0.24	B2
HDR2SN-06	3/8"	0.75	19.1	4,800	19,200	5.0	0.34	B2
HDR2SN-08	1/2"	0.88	22.2	4,000	16,000	7.0	0.43	B2
HDR2SN-10	5/8"	1.00	25.4	3,630	14,520	8.0	0.50	B2
HDR2SN-12	3/4"	1.16	29.4	3,120	12,480	9.5	0.61	B2
HDR2SN-16	1"	1.50	38.1	2,400	9,600	12.0	0.88	B2
HDR2SN-20	1-1/4"	1.88	47.7	1,820	7,280	16.5	1.52	S4/SG
HDR2SN-24	1-1/2"	2.13	54.1	1,310	5,240	20.0	1.64	S4/SG
HDR2SN-32	2"	2.63	66.7	1,160	4,640	25.0	2.02	S4/SG



HDR16 - HIGH TEMP/HIGH PRESSURE COMPACT TWO WIRE HOSE								
Exceeds the requirements of SAE 100R16; EN 857 2SC					TWO WIRE BRAID REINFORCEMENT			
CHLORINATED POLYETHYLENE INNER TUBE					CHLORINATED POLYETHYLENE OUTER COVER			
-40°F to 302°F (-40°C to 150°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HDR16-04	1/4"	0.54	18.8	5,075	20,300	2.0	0.23	B2
HDR16-06	3/8"	0.70	17.8	5,000	20,000	2.5	0.33	B2
HDR16-08	1/2"	0.82	20.9	5,000	20,000	3.5	0.43	B2
HDR16-12	3/4"	1.10	28.0	3,500	14,000	5.0	0.61	B2
HDR16-16	1"	1.42	35.9	2,700	10,800	6.0	0.94	B2

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB

HOSE

HOSE



HLR2SN - LOW TEMP MEIDUM PRESSURE TWO WIRE HOSE								
Exceed the requirements of SAE 100R2AT; EN 853 2SN					TWO WIRE BRAID RIENFORCEMENT			
NITRILE INNER TUBE					POLYCHLOROPRENE OUTER COVER			
-58°F to 212°F (-50°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HLR2SN-04	1/4"	0.58	14.7	5,000	20,000	4.0	0.25	B2
HLR2SN-06	3/8"	0.74	18.7	4,800	19,200	5.0	0.34	B2
HLR2SN-08	1/2"	0.86	21.8	4,000	16,000	7.0	0.43	B2
HLR2SN-10	5/8"	0.99	25.0	3,630	14,520	8.0	0.50	B2
HLR2SN-12	3/4"	1.14	29.0	3,120	12,480	9.5	0.61	B2
HLR2SN-16	1"	1.48	37.6	2,400	9,600	12.0	0.88	B2
HLR2SN-20	1-1/4"	1.88	47.7	1,820	7,280	16.5	1.52	S4/SG
HLR2SN-24	1-1/2"	2.13	54.1	1,310	5,240	20.0	1.64	S4/SG
HLR2SN-32	2"	2.63	66.7	1,160	4,640	25.0	2.02	S4/SG



HR12 - FOUR SPIRAL WIRE HOSE								
Exceed the requirements of SAE 100R12; EN 856 R12					FOUR SPIRAL WIRE REINFORCEMENT			
POLYCHLOROPRENE INNER TUBE					POLYCHLOROPRENE OUTER COVER			
-40°F to 250°F (-40°C to 121°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR12-06	3/8"	0.80	20.3	4,100	16,400	2.5	0.40	S4/SG
HR12-08	1/2"	0.94	23.8	4,100	16,400	3.5	0.52	S4/SG
HR12-10	5/8"	1.08	27.4	4,100	16,400	4.0	0.70	S4/SG
HR12-12	3/4"	1.21	30.7	4,100	16,400	4.7	0.81	S4/SG
HR12-16	1"	1.50	38.0	4,100	16,400	11.8	1.20	S4/SG
HR12-20	1-1/4"	1.85	47.0	4,100	16,400	16.5	1.70	S4/SG
HR12-24	1-1/2"	2.10	53.5	4,100	16,400	19.7	2.05	S4/SG
HR12-32	2"	2.60	66.7	4,100	16,400	25.0	2.82	S4/SG

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



HR13 - HIGH PRESSURE FOUR/SIX SPIRAL WIRE HOSE

HR13 - HIGH PRESSURE FOUR/SIX SPIRAL WIRE HOSE								
Exceed the requirements of SAE 100R13; EN 856 E13					FOUR/SIX SPIRAL WIRE REINFORCEMENT			
POLYCHLOROPRENE INNER TUBE					POLYCHLOROPRENE OUTER COVER			
-40°F to 250°F (-40°C to 121°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR13-12	3/4"	1.26	32.1	5,100	20,400	9.4	1.09	S6/SG
HR13-16	1"	1.52	38.7	5,100	20,400	11.8	1.42	S6/SG
HR13-20	1-1/4"	1.96	49.8	5,100	20,400	16.5	2.69	S6/SG
HR13-24	1-1/2"	2.25	57.3	5,100	20,400	19.7	3.35	S6/SG
HR13-32	2"	2.80	71.1	5,100	20,400	25.2	4.93	S6/SG



HR15 - VERY HIGH PRESSURE FOUR/SIX SPIRAL WIRE HOSE

HR15 - VERY HIGH PRESSURE FOUR/SIX SPIRAL WIRE HOSE								
Exceeds the requirements of SAE 100R15					FOUR/SIX SPIRAL WIRE REINFORCEMENT			
POLYCHLOROPRENE INNER TUBE					POLYCHLOROPRENE OUTER COVER			
-40°F to 250°F (-40°C to 121°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR15-08	1/2"	0.95	24.2	6,100	24,400	7.9	0.59	S6/SG
HR15-12	3/4"	1.26	32.0	6,100	24,400	10.4	1.09	S6/SG
HR15-16	1"	1.53	38.8	6,100	24,400	13.0	1.46	S6/SG
HR15-20	1-1/4"	1.89	48.0	6,100	24,400	17.5	2.41	S6/SG
HR15-24	1-1/2"	2.23	56.8	6,100	24,400	20.9	3.02	S6/SG
HR15-32	2"	2.84	72.0	6,100	24,400	23.6	4.35	S6/SG

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



H4SP - VERY HIGH PRESSURE FOUR SPIRAL HOSE

Exceeds the requirements of EN 856 4SP					FOUR SPIRAL WIRE REINFORCEMENT			
POLYCHLOROPRENE INNER TUBE					POLYCHLOROPRENE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
H4SP-06	3/8"	0.94	21.4	6,455	25,820	7.1	0.51	SG
H4SP-08	1/2"	0.97	24.6	6,020	24,080	9.0	0.58	SG
H4SP-10	5/8"	1.11	28.2	5,075	20,300	9.8	0.73	SG
H4SP-12	3/4"	1.27	32.2	5,510	22,040	11.8	0.98	SG
H4SP-16	1"	1.56	39.7	4,640	19,560	13.4	1.30	SG




H4SH - VERY HIGH PRESSURE SPIRAL HOSE

Exceeds the requirements of EN 856 4SH					FOUR SPIRAL WIRE REINFORCEMENT			
POLYCHLOROPRENE INNER TUBE					POLYCHLOROPRENE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
H4SH-12	3/4"	1.27	32.2	6,090	24,360	11.0	1.09	S6/SG
H4SH-16	1"	1.52	38.7	5,510	22,040	13.4	1.42	S6/SG
H4SH-20	1-1/4"	1.79	45.5	5,080	20,320	17.9	1.71	S6/SG
H4SH-24	1-1/2"	2.11	53.5	4,205	16,820	22.0	2.19	S6/SG
H4SH-32	2"	2.68	68.1	3,650	14,600	28.0	3.31	S6/SG

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



HR7 - THERMOPLASTIC HOSE

HR7 - THERMOPLASTIC HOSE								
Exceeds the requirements of SAE 100R7; EN 856 R7					SYNTHETIC FIBRE RIENFORCEMENT			
NYLON INNER TUBE					URETHANE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR7-02	1/8"	0.34	8.5	2,500	10,000	0.5	0.03	X-/T7
HR7-03	3/16"	0.43	10.8	3,000	12,000	0.8	0.05	X-/T7
HR7-04	1/4"	0.51	13.0	3,000	12,000	1.3	0.06	X-/T7
HR7-05	5/16"	0.59	15.1	2,500	10,000	1.8	0.07	X-/T7
HR7-06	3/8"	0.68	17.0	2,250	9,000	2.0	0.10	X-/T7
HR7-08	1/2"	0.82	20.7	2,000	8,000	3.0	0.14	X-/T7
HR7-12	3/4"	1.07	27.1	1,250	5,000	5.0	0.19	X-/T7
HR7-16	1"	1.34	34.0	1,000	4,000	8.0	0.26	X-/T7



HR8 - THERMOPLASTIC HOSE

HR8 - THERMOPLASTIC HOSE								
Exceeds the requirements of SAE 100R8; EN 856 R8					SYNTHETIC FIBRE RIENFORCEMENT			
NYLON INNER TUBE					URETHANE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR8-03	3/16"	0.52	13.1	5,000	20,000	1.5	0.08	X-/T8
HR8-04	1/4"	0.63	15.9	5,000	20,000	2.0	0.12	X-/T8
HR8-06	3/8"	0.77	19.4	4,000	16,000	2.5	0.15	X-/T8
HR8-08	1/2"	0.89	22.7	3,500	14,000	4.0	0.19	X-/T8

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



HR8R - REDUCED OD THERMOPLASTIC HOSE								
Exceeds the requirements of SAE 100R8; EN 856 R8					SYNTHETIC FIBRE RIENFORCEMENT			
NYLON INNER TUBE					URETHANE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR8R-03	3/16"	0.41	10.3	5,000	20,000	0.8	0.06	X-/T7
HR8R-04	1/4"	0.49	12.3	5,000	20,000	1.3	0.07	X-/T7
HR8R-06	3/8"	0.64	16.4	4,000	16,000	2.0	0.11	X-/T7
HR8R-08	1/2"	0.76	19.3	3,500	14,000	3.0	0.13	X-/T7



HR18 - CONSTANT PRESSURE THERMOPLASTIC HOSE								
Exceeds the requirements of SAE 100R18					SYNTHETIC FIBRE RIENFORCEMENT			
POLYESTER INNER TUBE					POLYESTER OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR18-04	1/4"	0.49	12.3	3,000	12,000	1.3	0.06	X-/T7
HR18-05	5/16"	0.61	15.5	3,000	12,000	1.5	0.09	X-/T7
HR18-06	3/8"	0.66	16.8	3,000	12,000	2.0	0.12	X-/T7
HR18-08	1/2"	0.85	21.6	3,000	12,000	3.5	0.15	X-/T7

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



HR7N - NON-CONDUCTIVE THERMOPLASTIC HOSE								
Exceeds the requirements of SAE 100R7; EN 856 R7					SYNTHETIC FIBRE RIENFORCEMENT			
POLYESTER INNER TUBE					URETHANE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR7N-02	1/8"	0.34	8.5	2,500	10,000	0.5	0.03	X-/T7
HR7N-03	3/16"	0.43	10.8	3,000	12,000	0.8	0.05	X-/T7
HR7N-04	1/4"	0.49	12.3	2,750	11,000	1.3	0.06	X-/T7
HR7N-05	5/16"	0.58	14.7	2,500	10,000	1.8	0.08	X-/T7
HR7N-06	3/8"	0.64	16.1	2,250	9,000	2.0	0.10	X-/T7
HR7N-08	1/2"	0.82	20.7	2,250	9,000	3.0	0.14	X-/T7
HR7N-12	3/4"	1.07	27.1	1,250	5,000	5.0	0.19	X-/T7
HR7N-16	1"	1.34	34.0	1,000	4,000	8.0	0.26	X-/T7



HR8N - NON-CONDUCTIVE THERMOPLASTIC HOSE								
Exceeds the requirements of SAE 100R8; EN 856 R8					SYNTHETIC FIBRE RIENFORCEMENT			
POLYESTER INNER TUBE					URETHANE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR8N-04	1/4"	0.63	15.9	5,000	20,000	2.0	0.12	X-/T8
HR8N-06	3/8"	0.77	19.4	4,000	16,000	2.5	0.15	X-/T8
HR8N-08	1/2"	0.89	22.7	3,500	14,000	4.0	0.19	X-/T8

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



HR8RN - REDUCED OD NON-CONDUCTIVE THERMOPLASTIC HOSE

Exceeds the requirements of SAE 100R8; EN 856 R8					SYNTHETIC FIBRE RIENFORCEMENT			
POLYESTER INNER TUBE					URETHANE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR8RN-03	3/16"	0.41	10.3	5,000	20,000	0.5	0.06	X-/T7
HR8RN-04	1/4"	0.49	12.3	5,000	20,000	1.3	0.07	X-/T7
HR8RN-06	3/8"	0.64	16.4	4,000	16,000	2.0	0.11	X-/T7
HR8RN-08	1/2"	0.76	19.3	3,500	14,000	3.0	0.13	X-/T7



HR7T - TWIN-LINE THERMOPLASTIC HOSE

Exceeds the requirements of SAE 100R7; EN 856 R7					SYNTHETIC FIBRE RIENFORCEMENT			
NYLON INNER TUBE					URETHANE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR7T-03	3/16"	0.43	10.8	3,000	12,000	0.8	0.09	X-/T7
HR7T-04	1/4"	0.51	13.0	3,000	12,000	1.3	0.11	X-/T7
HR7T-05	5/16"	0.59	15.1	2,500	10,000	1.8	0.14	X-/T7
HR7T-06	3/8"	0.67	17.0	2,250	9,000	2.0	0.19	X-/T7
HR7T-08	1/2"	0.82	20.7	2,000	8,000	3.0	0.28	X-/T7

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



HR8T - TWIN-LINE THERMOPLASTIC HOSE									
Exceeds the requirements of SAE 100R8; EN 856 R8					SYNTHETIC FIBRE RIENFORCEMENT				
NYLON INNER TUBE					URETHANE OUTER COVER				
-40°F to 212°F (-40°C to 100°C)									
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES	
HR8T-06	3/8"	0.77	19.4	4,000	16,000	2.5	0.30	X-/T8	
HR8T-08	1/2"	0.89	22.7	3,500	14,000	4.0	0.38	X-/T8	



HR8RT - REDUCED OD TWIN-LINE THERMOPLASTIC HOSE								
Exceeds the requirements of SAE 100R8; EN 856 R8					SYNTHETIC FIBRE RIENFORCEMENT			
NYLON INNER TUBE					URETHANE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR8RT-03	3/16"	0.41	10.3	5,000	20,000	0.8	0.11	X-/T7
HR8RT-04	1/4"	0.49	12.3	5,000	20,000	1.3	0.13	X-/T7
HR8RT-06	3/8"	0.65	16.4	4,000	16,000	2.0	0.22	X-/T7
HR8RT-08	1/2"	0.76	19.3	3,500	14,000	3.0	0.25	X-/T7

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



HR7NT - TWIN-LINE NON-CONDUCTIVE THERMOPLASTIC HOSE								
Exceeds the requirements of SAE 100R7; EN 856 R7					SYNTHETIC FIBRE RIENFORCEMENT			
POLYESTER INNER TUBE					URETHANE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR7NT-04	1/4"	0.49	12.3	2,750	11,000	1.3	0.12	X-/T7
HR7NT-05	5/16"	0.58	14.7	2,500	10,000	1.8	0.15	X-/T7
HR7NT-06	3/8"	0.64	16.1	2,250	9,000	2.0	0.19	X-/T7
HR7NT-08	1/2"	0.82	20.7	2,250	9,000	3.0	0.29	X-/T7



HR8RNT - REDUCED OD TWIN-LINE NON-CONDUCTIVE THERMOPLASTIC HOSE								
Exceeds the requirements of SAE 100R8; EN 856 R8					SYNTHETIC FIBRE RIENFORCEMENT			
POLYESTER INNER TUBE					URETHANE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR8RNT-03	3/16"	0.41	10.3	5,000	20,000	0.8	0.11	X-/T8
HR8RNT-04	1/4"	0.49	12.3	5,000	20,000	1.3	0.13	X-/T8
HR8RNT-06	3/8"	0.65	16.4	4,000	16,000	2.0	0.22	X-/T8
HR8RNT-08	1/2"	0.76	19.3	3,500	14,000	3.0	0.25	X-/T8

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



HLP - LOW PRESSURE PUSH-ON HOSE

HLP - LOW PRESSURE PUSH-ON HOSE								
Non-Conductive Hose, Good for fuel					ONE TEXTILE BRAID REINFORCEMENT			
NBR/PVC INNER TUBE					NITRILE RUBBER OUTER COVER			
-40°F to 190°F (-40°C to 88°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HLP-04	1/4"	0.54	13.7	300	1,200	2.5	0.09	X-/PO
HLP-05	5/16"	0.62	15.7	300	1,200	3.0	0.12	X-/PO
HLP-06	3/8"	0.69	17.5	300	1,200	3.0	0.14	X-/PO
HLP-08	1/2"	0.81	20.6	300	1,200	5.0	0.16	X-/PO
HLP-10	5/8"	0.93	23.6	300	1,200	6.0	0.20	X-/PO
HLP-12	3/4"	1.07	27.2	300	1,200	7.0	0.25	X-/PO
HLP-16	1"	1.34	34.0	300	1,200	8.0	0.34	X-/PO



HR3 - LOW PRESSURE HOSE

HR3 - LOW PRESSURE HOSE								
Exceeds the requirements of SAE 100R3/EN 854 R3					TWO TEXTILE BRAID REINFORCEMENT			
POLYCHLOROPRENE INNER TUBE					POLYCHLOROPRENE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR3-04	1/4"	0.56	14.3	1,250	5,000	3.0	0.12	X-
HR3-05	5/16"	0.68	17.5	1,200	4,800	4.0	0.16	X-
HR3-06	3/8"	0.75	19.0	1,125	4,500	4.0	0.17	X-
HR3-08	1/2"	0.94	23.8	1,000	4,000	5.0	0.25	X-
HR3-10	5/8"	1.06	27.1	884	3,538	5.5	0.31	X-
HR3-12	3/4"	1.25	31.8	750	3,000	6.0	0.43	X-
HR3-16	1"	1.50	38.1	565	2,260	8.0	0.51	X-

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



HR4 - SUCTION/LOW PRESSURE DISCHARGE HOSE

Exceeds the requirements of SAE 100R4					SPLRAL PLIED FABRIC WITH WIRE HELIX REINFORCEMENT			
NITRILE INNER TUBE					POLYCHLOROPRENE OUTER COVER			
-40°F to 275°F (-40°C to 135°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR4-12	3/4"	1.16	29.5	300	1,200	2.5	0.53	B2/X-
HR4-16	1"	1.45	36.8	250	1,000	3.0	0.65	B2/X-
HR4-20	1-1/4"	1.70	43.2	200	800	4.0	0.80	S4/SG/X-
HR4-24	1-1/2"	1.95	49.5	150	600	5.0	0.91	S4/SG/X-
HR4-32	2"	2.46	62.5	100	400	6.0	1.18	S4/SG/X-
HR4-40	2-1/2"	2.97	75.4	62	250	7.0	1.72	X-
HR4-48	3"	3.53	89.7	58	232	9.0	2.03	X-
HR4-64	4"	4.54	115.3	35	140	12.0	2.75	X-



HR5 - ONE WIRE FLEET HOSE

Exceeds the requirements of SAE 100R5 DOT FM					ONE WIRE BRAID REINFORCEMENT			
NITRILE INNER TUBE					TEXTILE BRAID OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR5-04	3/16"	0.52	13.2	3,000	12,000	3.0	0.15	FG/X-
HR5-05	1/4"	0.58	14.8	3,000	12,000	3.4	0.18	FG/X-
HR5-06	5/16"	0.68	17.1	2,250	9,000	4.0	0.22	FG/X-
HR5-08	13/32"	0.77	19.5	2,000	8,000	4.6	0.30	FG/X-
HR5-10	1/2"	0.92	23.4	1,750	7,000	5.5	0.37	FG/X-
HR5-12	5/8"	1.08	27.4	1,500	6,000	6.5	0.45	FG/X-
HR5-16	7/8"	1.24	31.4	800	3,200	7.4	0.47	FG/X-
HR5-20	1-1/8"	1.50	38.1	625	2,500	9.0	0.58	FG/X-
HR5-24	1-3/8"	1.75	44.4	500	2,000	10.5	0.73	FG/X-
HR5-32	1-13/16"	2.22	56.4	350	1,400	13.3	0.91	FG/X-

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



HR5HT - HIGH TEMPERATURE ONE WIRE FLEET HOSE

Exceeds the requirements of SAE 100R5 DOT FM					ONE WIRE BRAID REINFORCEMENT			
NITRILE INNER TUBE					TEXTILE BRAID OUTER COVER			
-40°F to 302°F (-40°C to 150°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR5HT-04	3/16"	0.52	13.2	3,000	12,000	3.0	0.15	FG/X-
HR5HT-05	1/4"	0.58	14.8	3,000	12,000	3.4	0.18	FG/X-
HR5HT-06	5/16"	0.68	17.1	2,250	9,000	4.0	0.22	FG/X-
HR5HT-08	13/32"	0.77	19.5	2,000	8,000	4.5	0.30	FG/X-
HR5HT-10	1/2"	0.92	23.4	1,750	7,000	5.5	0.37	FG/X-
HR5HT-12	5/8"	1.08	27.4	1,500	6,000	6.5	0.45	FG/X-
HR5HT-16	7/8"	1.24	31.4	800	3,200	7.4	0.47	FG/X-
HR5HT-20	1-1/8"	1.50	38.1	625	2,500	9.0	0.58	FG/X-



HR14 - STAINLESS/PTFE HOSE

Exceeds the requirements of SAE 100R14; FDA 21 CFR					304 STAINLESS STEEL WIRE BRAID REINFORCEMENT			
POLYTETRAFLUROETHYLENE(PTFE) INNER TUBE					304 STAINLESS STEEL WIRE BRAID OUTER COVER			
-65°F to 450°F (-54°C to 232°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HR14-03	3/16"	0.31	7.9	3,000	12,000	2.0	0.06	X-
HR14-04	1/4"	0.38	9.5	3,000	12,000	3.0	0.08	X-
HR14-05	5/16"	0.45	11.3	2,500	10,000	4.0	0.09	X-
HR14-06	3/8"	0.50	12.8	2,250	9,000	4.5	0.11	X-
HR14-08	1/2"	0.65	16.5	1,500	6,000	6.5	0.15	X-
HR14-10	5/8"	0.78	19.8	1,200	4,800	7.7	0.19	X-
HR14-12	3/4"	0.89	22.5	1,100	4,400	8.2	0.21	X-
HR14-16	1"	1.14	28.8	900	3,600	10.0	0.32	X-

Phone: 780-413-0904
 Fax: 780-413-0905
 Toll free: 1-800-239-0416



18141 - 111 Avenue
 T5S 2P2
 Edmonton, Alberta , AB



HJK - JACK HOSE								
FOR HIGH PRESSURE JACKING APPLICATIONS					TWO WIRE BRAID REINFORCEMENT			
NITRILE INNER TUBE					POLYCHLOROPRENE OUTER COVER			
-40°F to 212°F (-40°C to 100°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HJK-04	1/4"	0.58	14.7	10,000	20,000	4.0	0.24	B2
HJK-06	3/8"	0.74	18.7	10,000	20,000	5.0	0.30	B2



HAB - AIR BRAKE J1402 HOSE								
FOR AIR BRAKE APPLICATIONS					TWO SPIRAL SYNTHETIC REINFORCEMENT			
EPDM INNER TUBE					EPDM OUTER COVER			
-40°F to 200°F (-40°C to 93°C)								
PART NUMBER	ID	OD (in.)	OD (mm)	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS (in.)	WEIGHT/FT	FITTING SERIES
HAB-	1/4"	0.59	15.0	145	580	-	0.13	X-
HAB-	3/8"	0.75	19.1	145	580	-	0.17	X-
HAB-	1/2"	0.88	22.4	145	580	-	0.21	X-